

PRODUCT SPECIFICATIONS

1. PRODUCT IDENTIFICATION

GS PRO Ice and Water Protection

Item Code: GSPIW

2. GENERAL DESCRIPTION

Description: GS PRO is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability. Designed as a second wall of defense against wind driven rain and seepage due to ice damming. For use on decks 2:12 and greater.

3. PRODUCT ATTRIBUTES

Tested In Accordance With ASTM D1970:

PRODUCT SPECIFICATIONS		UNIT
Maximum Load, min	MD=25	lbf/inch
	CD=25	lbf/inch
Thickness, min	40 mils	mils
Elongation at Break, min	10%	%
Adhesion to Plywood @ 77F, min	12 lbf/ft	lbf/ft
Flexibility Temperature, @-20F min	Pass	
Nail Seal-ability	Pass	
Waterproof Integrity of Lap Seam	Pass	
Slip Resistance	Pass	
Rolls per Pallet (label)	30	
Rolls Weight	60+/-2	Lbs.
Roll Diameter	7.5	inch
Square Feet	195	
Roll Dimension	36"x65'	

4. LIMITATIONS

Good practice calls for the membrane to be covered as soon as practical. Not resistant to oils and solvents. Not designed for permanent exposure. Thin films of dust, water, frost, or ice will affect the skid resistance of this product and must be avoided. Do not use in contact with flexible PVC (Poly Vinyl Chloride) membranes. New dimensional lumber decks may contain knots with resin levels that can attack and severely soften the GS PRO bitumen compound.

5. PACKAGING

PACKAGING SPECIFICATIONS				
TYPE	ROLL SIZE	COVERAGE (ft ²)	PALLET QTY	TRUCKLOAD
ROLL	3' x 65'	195 sq ft	30	720

Scan the QR code to access additional information

