



# TS20 Synthetic Roofing Underlayment

SRS TopShield® TS20 Synthetic Underlayment is a preferred choice for sloped roof applications over felt paper.

SRS TopShield® TS20 Synthetic Underlayment is designed for maximum roofer comfort and productivity.

The lightweight 10 square rolls provide more coverage are easy to handle and faster to install than felt paper. The non-woven surface provides a better traction for your crew. **TRY IT TODAY!**



## UNDERLAYMENT FEATURES & BENEFITS

- Meets ASTM D226 Types I & II and D4869 Types II & IV
- Meets ASTM D8257
- Durable, slip-resistant walking surface
- 60 days UV exposure
- Up to 12 times stronger than #15 felt\*
- 6 squares more per roll than #15 felt\*\*
- Easy to install – 42" wide lightweight rolls
- Synthetic construction is inert to mold growth
- Lays flat and does not absorb water and wrinkle
- Advanced backside non-slip coating
- Low temperature flexibility
- CCRR-0355
- ASTM E108/UL790 Class A Fire Resistance (when installed under asphalt shingles)
- Florida Product Approval

### TECHNICAL DATA (Meets or exceeds the following test standards)

Test and Standard	Test Method
Breaking Strength	ASTM D146
Pliability	ASTM D146
Loss of Heating	ASTM D146
Unrolling	ASTM D226
Liquid Water Transmission	ASTM D4869
Tear Resistance	ASTM D4073
Dimensional Stability	ASTM F1087
Moisture Vapor Permeance	ASTM E96
Burst Strength	ASTM D751
Class A Fire <sup>^</sup>	ASTM E108

ROLL & PALLET SPECS	
Length per Roll	286' / 87 m
Width per Roll	42" / 1.1 m
Nominal Weight per Roll	23.5 lbs / 10.6 kg***
Roll Size	10 sq / 93 m <sup>2</sup>
Rolls per Pallet	67
Pallet Weight	1,626 lbs / 738 kg



Scan the QR code to access additional information.

<sup>^</sup> When installed under asphalt shingles.

\* Test data is based on average of samples tested in accordance with ASTM D2261.

\*\* Coverage per roll is 9.09 sq with a 4" horizontal overlap.

\*\*\* Incluye el peso del núcleo.