

## TSDA-4 DECK-AIR™ ROOF DECK INTAKE VENT

## **PRODUCT SPECIFICATIONS**

## 1.1 MATERIALS:

1.1.1 Plastic Polymers:

Custom blended, high impact co-polymer with UV stabilization additives.

**1.2.1 Screen:** 18 Mesh Fiberglass Screen.

## 2. MISCELLANEOUS:

- 1.2.1 Description: Injection molded, shingle over roof intake. Packaged with 30 2-½" corrosion resistant ring shank nails per part (300 per box). Molded in 4 foot sections. Can be installed on roof pitches from 3/12 to 16/12. Features unique design that provides enhanced weather protection, integrated end plugs every 2 inches, molded nail lines, and fully supported nail holes. This is an intake vent and must be used in conjunction with adequate exhaust vents for proper operation.
- **1.2.2** Color: Available BLACK.
- **1.2.3** Net Free Area: 9 square inches per linear foot. (36 square inches per 4 foot part.)
- **1.2.4** Packaging: Packaged 10 to a carton. Available in 4 foot lengths. UPC labels are affixed to each vent and carton.
- **1.2.5 Warranty:** Limited lifetime warranty.
- **1.2.6 Performance:** Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.
- **1.2.7 Approvals:** Miami-Dade County Approved NOA No: 20-0908.06, expires: 07/10/24. Texas Department of Insurance "Windstorm" Approved Product Evaluation Report No: RV-115.

Revised on 8/21/2022

