

TSLOR-30 FEATURES

- · Pneumatic nail gun or hammer installed
- Two coils of 1 3/4" nails provided
- Patented design brings you the truly functional roll out
- Compact 30 foot roll is easy to handle
- Superior weather protection and performance with no filter to clog
- Exterior convolute baffles incurved design allows flexibility to roll up and out while maintaining its shape
- Can be cut at one foot intervals multiple cut lines eliminates unnecessary scrap
- Patented molded fanfold end plugs no accessories or alterations needed
- Molded centerline for fast and easy alignment
- Field tested design proven effective under all weather conditions
- The air flow acceleration design maximizes ventilation capacity
- Omni baffles signify air flow from any direction
- Nail holes marked every 6 inches supported every foot - will not crush down
- Full 11 square inches of net free area per linear foot
- Engineered material guarantees longevity.
- Lifetime Limited Warranty

- 1. Compact roll for easy handling
- 2. Louvers close to wind stream
- 3. Convolute exterior baffle design
- **4.** Innovative aerodynamic curved internal baffles
- 5. Unique omni baffles enhance airflow from any direction
- 6. Molded-In end plug

SPECIFICATIONS		
Model	Packaged	
TSLOR-30	1 Per Carton	

Length	Roof Pitch	NFA
(ft.)	(in.)	(in.²)
30	2/12 to 16/12	









Revised on 8/31/2022

Scan the QR code to access additional information

