



**TSLOR9-4FR FEATURES**

- Sonic welded fiberglass screen provides enhanced weather protection
- Includes 2 1/2" ring shank nails, 30 nails per piece
- Pneumatic nail gun or hammer installed
- Four drain holes per side per foot
- 11 square inches of Net Free Area per linear foot
- External venturi baffle
- Nail holes marked every 6 inches - supported every foot
- Preformed to 3/12 pitch
- Fits roof pitches 2/12 to 16/12
- Molded nail lines
- Molded centerline for fast and easy alignment
- Alignment tabs
- External water shield

- Slot width guide lines
  - Patented molded-in fanfolded endplug fits all roof pitches
  - **Lifetime Limited Warranty**
1. Full UL mark included on vent
  2. Aerodynamically curved internal baffles to minimize wind resistance
  3. Unique OmniRidge<sup>®</sup> perpendicular baffles enhance airflow
  4. Louvers positioned closer to wind stream for better airflow
  5. Molded-in endplug
  6. Weatherproof under-lapping joint prohibits weather infiltration



Want more info? Scan the QR code to access additional information on [TopShieldProducts.com](http://TopShieldProducts.com)

SPECIFICATIONS				
Model	Length (ft.)	Roof Pitch	NFA (in. <sup>2</sup> )	Packaged
TSLOR9-4FR	4	2/12 to 16/12	44	10 per box