



## TSPRO4-N FEATURES

- Advanced low profile design
- Includes 2 1/2" ring shank nails, 30 nails per piece
- Internal baffles
- External "Omni" baffles
- External Venturi baffle
- "Posi-tabs" contour to shingles for improved weather protections
- Weatherproof underlapping joints
- 6 drain holes per side per foot
- 18 square inches of Net Free Area per linear foot
- 10 supported nail holes
- Preformed to 2/12 pitch
- Fits roof pitches 2/12 to 16/12
- Molded-in shingle nail lines, reinforced every 2 inches
- Slot width guide lines
- Continuous molded end plug for improved weather protection
- **Lifetime Limited Warranty**

1. External Venturi and "Omni" baffles provide enhanced airflow
2. Fully supported nail holes
3. Unique "posi-tabs" contour to shingles for improved weather protection
4. Continuous molded end plug and underlap prohibit weather infiltration



Net Free  
Area Verified



Texas Department of  
Insurance "Windstorm"  
Approved

SPECIFICATIONS		
Model	Packaged	
TSPRO4N	10 Per Box	
Length (ft.)	Roof Pitch (in.)	NFA (in.-2)
4	2/12 to 16/12	72

Revised on 8/30/2022

Scan the QR code  
to access additional  
information

