



TSPRO4-N FEATURES

- Advanced low profile design
- Includes 2 1/2" ring shank nails, 30 nails per piece
- Internal baffles
- External "Omni" baffles
- External Venturi baffle
- "Posi-tabs" contour to shingles for improved weather protections
- Weatherproof underlapping joints
- 6 drain holes per side per foot
- 18 square inches of Net Free Area per linear foot
- 10 supported nail holes
- Preformed to 2/12 pitch
- Fits roof pitches 2/12 to 16/12
- Molded-in shingle nail lines, reinforced every 2 inches
- Slot width guide lines
- Continuous molded end plug for improved weather protection
- **Lifetime Limited Warranty**

1. External Venturi and "Omni" baffles provide enhanced airflow
2. Fully supported nail holes
3. Unique "posi-tabs" contour to shingles for improved weather protection
4. Continuous molded end plug and underlap prohibit weather infiltration



Net Free
Area Verified



Texas Department of
Insurance "Windstorm"
Approved

| SPECIFICATIONS | | |
|----------------|------------------|-------------------------|
| Model | Packaged | |
| TSPRO4N | 10 Per Box | |
| Length (ft.) | Roof Pitch (in.) | NFA (in. ²) |
| 4 | 2/12 to 16/12 | 72 |

Revised on 8/30/2022

Escanear el código QR para acceder adicional información.

